

# F2/F2-BT Field Recorder Specifications

## INPUT

CONNECTOR:	3.5 mm stereo mini (with screw lock) Supports plug-in power (2.5 V)
INPUT GAIN:	None (dual AD conversion system)
INPUT IMPEDANCE:	2 k $\Omega$ or more
MAXIMUM INPUT LEVEL:	-5.5 dBu

## OUTPUT

CONNECTOR:	3.5 mm stereo mini (with screw lock)
MAXIMUM OUTPUT LEVEL:	20 mW + 20 mW (into 32 $\Omega$ load)

## RECORDING MEDIA

CARDS COMPATIBLE WITH MICROSD/  
MICROSDHC/  
MICROSDXC SPECIFICATIONS (CLASS 4  
OR HIGHER, 512 GB MAXIMUM)

## RECORDING FORMAT

WAV:	44.1kHz/32-bit float, 48kHz/32-bit float Mono, BWF format supported
------	---

## USB

USB TYPE-C	
MASS STORAGE OPERATION	USB 2.0 High Speed
PC APP OPERATION	USB 2.0 High Speed

## POWER

2 AAA BATTERIES (ALKALINE, LITHIUM  
OR RECHARGEABLE NIMH BATTERIES)  
AC ADAPTER (ZOOM AD-17): DC 5 V/1 A

## MISCELLANEOUS

BLUETOOTH:	Bluetooth Ver4.2 (F2-BT only)
CONTINUOUS RECORDING TIME WHEN USING LAVALIER MIC (48KHZ/32-BIT FLOAT):	Alkaline batteries: about 14 hours  NiMH batteries (750 mAh): about 10 hours Lithium batteries: about 18 hours  • The above values are approximate.
EXTERNAL DIMENSIONS:	57.5 mm (W) × 46.4 mm (H) × 22.4 mm (D)
WEIGHT (MAIN UNIT ONLY):	32 g